



Publication Year	1998
Acceptance in OA	2023-02-10T13:42:34Z
Title	TC/TM DATABASE FOR THE EPIC MOS CAMERA SYSTEM (EMCS)
Authors	LA PALOMBARA, NICOLA
Handle	http://hdl.handle.net/20.500.12386/33400

EMCS CONDITION PARAMETERS

EPIC-EST-TN-008 I.2

Appendix K

PREF	NAME	DESCRIPTION	DEFINITION
X4000	Idle mode	This condition parameter indicates that the system is in Idle mode	K1008 = 1
X4001	SafeStandBy mode	This condition parameter indicates that the system is in Safe Stand-by mode.	K1008 = 0
X4002	I or IFT mode	This condition parameter indicates that the system is in Idle or in In-Flight Test mode	K1008 = 1 OR K1008 = 16
X4003	InFlightTestMode	This condition parameter indicates that the system is in In-Flight Test mode	K1008 = 16
X4004	SSB or IFT mode	This condition parameter indicates that the system is in Safe Stand-by or in In-Flight Test mode	K1008 = 0 OR K1008 = 16
X4005	SSB/I/IFT mode	This condition parameter indicates that the system is in Safe Stand-By or in Idle or in In-Flight Test mode	K1008 = 0 OR K1008 = 1 OR K1008 = 16
X4006	ExtraheatingMode	This condition parameter indicates that the system is in Extraheating mode	K1008 = 6