



Publication Year	1999
Acceptance in OA	2023-02-10T13:14:59Z
Title	TC/TM DATABASE FOR THE EPIC PN CAMERA SYSTEM (EPCS)
Authors	LA PALOMBARA, NICOLA
Handle	http://hdl.handle.net/20.500.12386/33399

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0001	Offset/Noise Sel	2	8	8	V	n/a		1	16
Selection of the Offset or Noise Map computation									

RAW VALUE	MEANING
1	Offset Table
16	Noise Table

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0002	Readout Number	3	4	8	V	n/a		1	100
Number of readouts to be used in the Offset/Noise computation									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0003	CCD Start Line	3	12	16	V	n/a		0	196
First CCD line to be considered									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0004	CCD Stop Line	3	12	16	V	n/a		0	196
Last CCD line to be considered									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0005	CCD identifier	2	4	4	V	n/a		0	2
This parameter identifies the number of the selected CCD									

RAW VALUE	MEANING
------------------	----------------

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0006	ReadoutFrameNumb	3	12	16	V	n/a		1	100
Number of frames to be readout									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0007	Min Temp Mon Val	3	4	8	V	n/a			
Minimum value of the temperature monitoring									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0008	Max Temp Mon Val	3	4	8	V	n/a			
Maximum value of the temperature monitoring									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0009	InFlightTestMode	2	0	16	V	n/a		0	1
Selected In-flight Test Mode									

RAW VALUE	MEANING
0	EPCS
1	EPDH

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0010	Proc/Task Ident.	2	0	16	V	n/a			
Identifier of the EPDH process or task									

RAW VALUE MEANING

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0011	Locking Time	3	12	16	V	n/a			
Locking Time of the specified EPDH task									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0012	EPDH TaskStartAd	3	12	16	V	n/a			
Start address for the EPDH task loading									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0013	OverrunTolerance	2	0	16	V	n/a			
Overrun Tolerance of the specified EPDH task									

RAW VALUE MEANING

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0014	MaxOvrrunCounter	3	12	16	V	n/a			
Maximum Overrun Counter of the specified EPDH task									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0015	EPDHTaskPriority	3	12	16	V	n/a		0	255
Priority of the specified EPDH task									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0016	EPDH Task Period	3	12	16	V	n/a			
Period of the specified EPDH periodic task									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0017	EPDH Task Phase	3	12	16	V	n/a			
Phase of the specified EPDH periodic task									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0018	EPDH Task Status	2	0	16	V	n/a			
Status of the specified EPDH periodic task									

RAW VALUE MEANING

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0019	HBR1 SelecStatus	2	1	1	V	n/a		0	1
Selection status of HBR 1									

RAW VALUE MEANING

0 Not Selected

20/09/1999

EPIC SYSTEM TEAM

Page 2 of 21

EPIC-EST-TN-005 I.3
Appendix E

20/09/1999

EPIC-EST-TN-005 I.3
Appendix E

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

EPICS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0033	HBR 1 CCD 2 mode	2	4	4	V	n/a		0	5
Operating mode of CCD2 in HBR 1 (Quadrant 0)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0034	HBR 2 CCD 0 mode	2	4	4	V	n/a		0	5
Operating mode of CCD0 in HBR 2 (Quadrant 1)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0035	HBR 2 CCD 1 mode	2	4	4	V	n/a		0	5
Operating mode of CCD1 in HBR 2 (Quadrant 1)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0036	HBR 2 CCD 2 mode	2	4	4	V	n/a		0	5
Operating mode of CCD2 in HBR 2 (Quadrant 1)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0037	HBR 3 CCD 0 mode	2	4	4	V	n/a		0	5
Operating mode of CCD0 in HBR 3 (Quadrant 2)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF
2	Imaging LW
3	Imaging SW
4	Timing
5	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0038	HBR 3 CCD 1 mode	2	4	4	V	n/a		0	5
Operating mode of CCD1 in HBR 3 (Quadrant 2)									

RAW VALUE	MEANING
0	Not Active
1	Imaging FF

20/09/1999

EPIC SYSTEM TEAM

Page 5 of 21

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

- 2 Imaging LW
- 3 Imaging SW
- 4 Timing
- 5 Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0039	HBR 3 CCD 2 mode	2	4	4	V	n/a		0	5
Operating mode of CCD2 in HBR 3 (Quadrant 2)									

RAW VALUE MEANING

- 0 Not Active
- 1 Imaging FF
- 2 Imaging LW
- 3 Imaging SW
- 4 Timing
- 5 Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0040	HBR 4 CCD 0 mode	2	4	4	V	n/a		0	5
Operating mode of CCD0 in HBR 4 (Quadrant 3)									

RAW VALUE MEANING

- 0 Not Active
- 1 Imaging FF
- 2 Imaging LW
- 3 Imaging SW
- 4 Timing
- 5 Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0041	HBR 4 CCD 1 mode	2	4	4	V	n/a		0	5
Operating mode of CCD1 in HBR 4 (Quadrant 3)									

RAW VALUE MEANING

- 0 Not Active
- 1 Imaging FF
- 2 Imaging LW
- 3 Imaging SW
- 4 Timing
- 5 Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0042	HBR 4 CCD 2 mode	2	4	4	V	n/a		0	5
Operating mode of CCD2 in HBR 4 (Quadrant 3)									

RAW VALUE MEANING

- 0 Not Active
- 1 Imaging FF
- 2 Imaging LW
- 3 Imaging SW
- 4 Timing
- 5 Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0043	HBR1BuffStartAdd	3	14	32	V	n/a			
Start address of HBR 1 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0044	HBR1 BuffEndAdd	3	14	32	V	n/a			
End address of HBR 1 buffer									

CALIBRATION CURVE

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0045	HBR2BuffStartAddr	3	14	32	V	n/a			
Start address of HBR 2 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0046	HBR2 BuffEndAddr	3	14	32	V	n/a			
End address of HBR 2 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0047	HBR3BuffStartAddr	3	14	32	V	n/a			
Start address of HBR 3 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0048	HBR3 BuffEndAddr	3	14	32	V	n/a			
End address of HBR 3 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0049	HBR4BuffStartAddr	3	14	32	V	n/a			
Start address of HBR 4 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0050	HBR4 BuffEndAddr	3	14	32	V	n/a			
End address of HBR 4 buffer									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0051	TherMonUppTemLim	3	4	8	V	n/a			
Upper temperature limit checked by the EPDH during the normal operating thermal control of the focal plane									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0052	TherMonLowTemLim	3	4	8	V	n/a			
Lower temperature limit checked by the EPDH during the normal operating thermal control of the focal plane									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0053	Activation Time	3	4	8	V	sec		0	255
Activation time of the Door / Venting Valve power arming									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0054	EPEA Preset Time	3	12	16	V	sec		1	32400
Preset value of the counter used for the automatic generation of the reset pulse to the EPEA during observation									

CALIBRATION CURVE

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3

Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0058	NoOperLoopRepet	3	12	16	V	n/a		0	65535
Number of times a no-operation loop has to be executed before the next data are sent over the HBR									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0059	SegmentStartAddr	3	12	16	V	n/a			
Segment start address for the EPEA/EPCE RAM checksum calculation and the EPEA memory area filling									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0060	OffsetStartAddr	3	12	16	V	n/a			
Offset start address for the EPEA/EPCE RAM checksum calculation and the EPEA memory area filling									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0061	MemoryAreaLength	3	12	16	V	n/a			
Length (in bytes) of the memory area to be considered for the EPEA/EPCE RAM checksum calculation and the EPEA memory area filling									
If this parameter is set to 0, the RAM check is progress is stopped.									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0062	ScientificEventN	3	12	16	V	n/a		0	65535
Number of scientific events to be sent through the HBR I/F									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0063	NumbTransmFrames	3	12	16	V	n/a		1	65535
Number of test picture frames to be transmitted through the HBR I/F									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0064	Table Stop Block	3	12	16	V	n/a			
Stop block for the transmission of the Offset / Noise / Discarded Line Tables Allowed range of values:									
1) 0 - 216 for the Offset & Noise Tables;									
2) 0 - 3 for the Discarded Line Table.									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0065	ScientTableSelec	2	0	16	V	n/a		0	256
Selection of the scientific table									

RAW VALUE	MEANING
1	Offset Table
16	Noise Table

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0066	Table StartBlock	3	12	16	V	n/a			
Start block for the transmission of the Offset / Noise / Discarded Line Tables Allowed range of values:									
1) 0 - 216 for the Offset & Noise Tables;									
2) 0 - 3 for the Discarded Line Table.									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0067	SegmentJumpAddr	3	12	16	V	n/a			
Segment address of the jump to perform in the EPEA/EPCE program									

CALIBRATION CURVE

20/09/1999

EPIC SYSTEM TEAM

Page 8 of 21

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0068	Offset Jump Addr	3	12	16	V	n/a			
Offset address of the jump to perform in the EPEA/EPCE program									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0069	8-bit data	3	4	8	V	n/a		0	255
Byte data to be loaded in the selected EPEA/EPCE RAM location									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0070	16-bit data	3	12	16	V	n/a		0	65535
Word data to be loaded in the selected EPEA/EPCE RAM/port location For the CE/EAIOWR only the LSB is significative if the Byte Data is selected									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0071	Register Select	2	0	16	V	n/a		0	2
Selection of the Segment or Offset or I/O register									

RAW VALUE MEANING

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0072	Seg Off I/O Addr	3	12	16	V	n/a			
Segment or Offset or I/O address (depending on the previous selection)									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0073	Data Selection	2	0	16	F	n/a			
This parameter allows to select if a byte or a word has to be written/read in/from a previously selected EPEA/EPCE I/O location									

RAW VALUE MEANING

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0074	MIP's Threshold	3	12	16	V	n/a		0	4095
MIP's high threshold in the selected EPEA quadrants									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0075	WritingVerificat	2	1	1	V	n/a		0	1
Status of the verification writing for the EPEA/EPCE data modify mode									

RAW VALUE	MEANING
0	Yes
1	No

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0076	Address Autoincr	2	1	1	V	n/a		0	1
Status of the address autoincrement for the EPEA/EPCE data modify mode									

RAW VALUE	MEANING
0	Off
1	On

EPICS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3

Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0077	Data Update Mode	2	1	1	V	n/a		0	1
Updating mode of the content of Ax/CE_DATA for the EPEA/EPCE data modify mode (meaningful only if PREF 0075 = 1)									

RAW VALUE	MEANING
0	One time
1	Continuously

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0078	EPEA ProgramMode	2	0	16	V	n/a		0	2
Selection of the EPEA Program Mode for the selected quadrants									

RAW VALUE	MEANING
0	Idle
1	Send
2	Debug

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0079	Corrective Value	3	12	16	V	n/a			
Corrective value to be set in the selected EPEA quadrants in order to process only positive values of energy									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0080	Low Thr CCD Sel	2	0	16	V	n/a		1	256
CCD selection for the setting of the lower threshold energy setting									

RAW VALUE	MEANING
1	CCD 2
16	CCD 1

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0081	LowerThreshValue	3	12	16	V	n/a		0	4095
Value of the lower threshold energy									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0082	LowerUpperLimSel	2	0	16	V	n/a		1	16
Selection of the lower or upper standard deviation limit									

RAW VALUE	MEANING
1	Lower Limit
16	Upper Limit

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0083	StandDeviatValue	3	12	16	V	n/a		0	4095
Standard deviation limit									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0084	Undersampl. Rate	3	12	16	V	n/a		0	31
Undersampling rate (1 frame every N) of the incoming events									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0085	CCD 0 status	2	1	1	V	n/a		0	1
Off/On status of CCD 0 in the selected EPEA quadrants									

RAW VALUE	MEANING
0	Off
1	On

20/09/1999

EPIC SYSTEM TEAM

Page 10 of 21

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0086	CCD 1 status	2	1	1	V	n/a		0	1
Off/On status of CCD 1 in the selected EPEA quadrants									

RAW VALUE	MEANING
0	Off
1	On

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0087	CCD 2 status	2	1	1	V	n/a		0	1
Off/On status of CCD 2 in the selected EPEA quadrants									

RAW VALUE	MEANING
0	Off
1	On

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0088	CCDs ReadoutMode	2	0	16	V	n/a		32	36
Readout mode for all the CCDs of the selected EPEA quadrants									

RAW VALUE	MEANING
32	Full Frame
33	Small Window
34	Large Window
35	Timing
36	Burst

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0089	MIPCorrectionMod	2	0	16	V	n/a		16	18
MIP rejection mode for all the CCDs of the selected EPEA quadrants									

RAW VALUE	MEANING
16	MIP correc.1
17	MIP correc.2
18	No MIP corr.

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0090	Rejected Lines	3	12	16	V	n/a		0	100
Number of lines to be rejected below and above the MIP									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0091	LowLeftCornerCCD	3	12	16	V	n/a		0	2
CCD at the window low left corner									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0092	LowLeftCornerLin	3	12	16	V	n/a		0	199
CCD line at the window low left corner									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0093	UpRightCornerCCD	3	12	16	V	n/a		0	2
CCD at the window up right corner									

CALIBRATION CURVE

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0094	UpRightCornerLin	3	12	16	V	n/a		0	199
CCD line at the window up right corner									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0095	Pixel Status	2	8	8	V	n/a		1	16
Good/Bad status of a single pixel									

RAW VALUE	MEANING								
1	Good								
16	Bad								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0097	CCD Pixel Line	3	4	8	V	n/a		0	199
Pixel line to be selected in the considered CCD									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0098	CCD Pixel Column	3	4	8	V	n/a		0	63
Pixel column to be selected in the considered CCD									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0099	ColumnLineStatus	2	4	4	V	n/a		0	1
Status of all the pixels in the selected CCD column/line									

RAW VALUE	MEANING								
0	Good								
1	Bad								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0100	MedianCorrecStat	2	0	16	V	n/a		1	16
Status of the median correction in the selected EPEA quadrants									

RAW VALUE	MEANING								
1	On								
16	Off								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0101	Cycles Number	3	12	16	V	n/a		0	65535
Number of cycles after which the "Count Info" is sent									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0102	Port Address	3	12	16	V	n/a			

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0103	Value To Add	3	12	16	V	n/a			
Constant value to be added to all the calculated offset values of a CCD column									

CALIBRATION CURVE

EPICS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3

Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0104	Save/LoadOffsetT	2	1	1	V	n/a		0	1
This parameter is used to select the saving or loading of one previously calculated offset table to/from RAM memory									

RAW VALUE	MEANING
0	Save
1	Load

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0105	EPCE Message	3	12	16	V	n/a		0	65535
With this parameter it is possible to set a message in the EPCE H/K location CE_MSG									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0106	Debug Mode	2	8	8	V	n/a		0	255
This parameter is used to enter in the EPCE the Debug Mode or to give the Debug level									

RAW VALUE	MEANING
0	Not Selected
255	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0107	Quadrant 0 Selec	2	1	1	V	n/a		0	1
Selection status of EPEA quadrant 0									

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0108	Quadrant 1 Selec	2	1	1	V	n/a		0	1
Selection status of EPEA quadrant 1									

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0109	Quadrant 2 Selec	2	1	1	V	n/a		0	1
Selection status of EPEA quadrant 2									

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0110	Quadrant 3 Selec	2	1	1	V	n/a		0	1
Selection status of EPEA quadrant 3									

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0111	MasterSeqClockSt	2	1	1	V	n/a		0	1
Selected status of the Master Sequencer Clock (Disabled/Enabled)									

RAW VALUE	MEANING
0	Disabled
1	Enabled

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0112	QuadrantsReadout	2	1	1	V	n/a		0	1
Selected mode for the quadrant readout (parallel/sequential)									

RAW VALUE	MEANING
-----------	---------

20/09/1999

EPIC SYSTEM TEAM

Page 13 of 21

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

0	Parallel								
1	Sequential								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0113	QuadReadTimeInte	3	0	4	V	n/a			
Time interval between readout of quadrants									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0114	Slave Address	3	0	4	V	n/a			

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0115	Register Address	3	0	4	V	n/a			

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0116	FW Timeout	3	12	16	V	n/a		0	2047
Timeout value (in steps) for the Filter Wheel control									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0117	FilterWheelStat	2	0	16	V	n/a		0	1
Selected status of the filter wheel (stop/running)									

RAW VALUE	MEANING
0	Stop
1	Start

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0118	FWMovemDirection	2	0	16	V	n/a		0	1
Direction of the filter wheel movement									

RAW VALUE	MEANING
0	To Close
1	To Open

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0119	FW EmergencyMode	2	0	16	V	n/a		0	1
This parameter is used to enable/disable the emergency mode for the FW									

RAW VALUE	MEANING
0	Normal
1	Emergency

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0120	Mode Selection	2	0	16	V	n/a		0	1
This parameter is used in various TCs to enable or disable the involved function									

RAW VALUE	MEANING
0	Disabled
1	Enabled

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0121	FW Position	2	0	16	V	n/a		0	5
Requested position of the FW									

RAW VALUE	MEANING
0	Open

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

- 1 Filter D
- 2 Filter C
- 3 Filter B
- 4 Filter A
- 5 Close
- 7 No Stop Pos.

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0122	FW MovementSpeed	2	0	16	V	n/a		0	1
Movement speed applied to the filter wheel (slow/fast)									

RAW VALUE	MEANING
0	Slow
1	Fast

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0123	RegulationTemper	3	12	16	V	n/a			
Regulation temperature setting (in K) to be used for the operating or decontamination heater thermal control									

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0124	PowerSwitchSelec	2	0	16	V	n/a		0	7
This parameter is used to select which converter or switch must be powered on/off									

RAW VALUE	MEANING
0	Quadr 0 Conv
1	Quadr 1 Conv
2	Quadr 2 Conv
3	Quadr 3 Conv
4	OperHeatConv
5	FiltWheelPow
6	DecHeat1Pow
7	DecHeat2Pow

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0125	On/Off Status	2	0	16	V	n/a		0	1
Setting of the On/Off status of the selected switches									

RAW VALUE	MEANING
0	Not Active
1	Active

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0126	DecHeat2PWStatus	2	1	1	V	n/a		0	1
Power status of the Decontamination Heater 2									

RAW VALUE	MEANING
0	Not Active
1	Active

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0127	DecHeat1PWStatus	2	1	1	V	n/a		0	1
Power status of the Decontamination Heater 1									

RAW VALUE	MEANING
0	Not Active
1	Active

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0128	FW Power Status	2	1	1	V	n/a		0	1
Filter Wheel power status									

RAW VALUE	MEANING
0	Not Active
1	Active

EPICS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0129	OperHeatConvStat	2	1	1	V	n/a		0	1
Power status of the Operating Heater converter									
RAW VALUE	MEANING								
0	Not Active								
1	Active								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0130	Quadr3ConvStatus	2	1	1	V	n/a		0	1
Power status of the Quadrant 3 converter									
RAW VALUE	MEANING								
0	Not Active								
1	Active								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0131	Quadr2ConvStatus	2	1	1	V	n/a		0	1
Power status of the Quadrant 2 converter									
RAW VALUE	MEANING								
0	Not Active								
1	Active								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0132	Quadr1ConvStatus	2	1	1	V	n/a		0	1
Power status of the Quadrant 1 converter									
RAW VALUE	MEANING								
0	Not Active								
1	Active								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0133	Quad0PowerStatus	2	1	1	V	n/a		0	1
Power status of the Quadrant 0 converter									
RAW VALUE	MEANING								
0	Not Active								
1	Active								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0134	OperHeatConvSele	2	1	1	V	n/a		0	1
This parameter is used to select the Operating Heater Converter									
RAW VALUE	MEANING								
0	Not Selected								
1	Selected								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0135	Qua3HiVolConvSel	2	1	1	V	n/a		0	1
This parameter is used to select the Quadrant 3 High Voltage Converter									
RAW VALUE	MEANING								
0	Not Selected								
1	Selected								
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0136	Qua2HiVolConvSel	2	1	1	V	n/a		0	1
This parameter is used to select the Quadrant 2 High Voltage Converter									
RAW VALUE	MEANING								
0	Not Selected								
1	Selected								

EPICS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0137	Qua1HiVolConvSel	2	1	1	V	n/a		0	1

This parameter is used to select the Quadrant 1 High Voltage Converter

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0138	Qua0HiVolConvSel	2	1	1	V	n/a		0	1

This parameter is used to select the Quadrant 0 High Voltage Converter

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0139	ConvDigitalLevel	3	4	8	V	n/a		0	255

Requested Digital Level for the EPVC converter setting

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0140	StaticVoltageSel	2	4	4	V	n/a		2	11

Selection of the static voltage to be set

RAW VALUE	MEANING
2	Cn_UAMOS_L
3	Cn_UAMOS_H
4	Cn_RFGA_L
5	Cn_RFGA_H
6	Cn_UPHI_L
7	Cn_UPHI_H
8	Cn_UFLSH_L
9	Cn_UFLSH_H
11	Cn_UVBST

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0141	StaticVoltDigSet	3	0	4	V	n/a		0	15

Requested Digital Level for the selected Static Voltage

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0142	UVAR OffsetSelect	2	1	1	V	n/a		0	1

Selection status of the UVAR Offset

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0143	CCD FFDR Select	2	1	1	V	n/a		0	1

Selection status of CCD FFDR

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0144	CCD BIAS Select	2	1	1	V	n/a		0	1

Selection status of CCD BIAS

RAW VALUE	MEANING
0	Not Selected
1	Selected

20/09/1999

EPIC SYSTEM TEAM

Page 17 of 21

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0145	CAMEX/TIMEX Sel	2	1	1	V	n/a		0	1
Selection status of CAMEX/TIMEX power									
RAW VALUE		MEANING							
0		Not Selected							
1		Selected							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0146	UVAR Offset Stat	2	1	1	V	n/a		0	1
Activation status of UVAR Offset									
RAW VALUE		MEANING							
0		Not Active							
1		Active							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0147	CCD FFDR Status	2	1	1	V	n/a		0	1
Activation status of CCD FFDR									
RAW VALUE		MEANING							
0		Not Active							
1		Active							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0148	CCD BIAS Status	2	1	1	V	n/a		0	1
Activation status of CCD BIAS									
RAW VALUE		MEANING							
0		Not Active							
1		Active							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0149	CAMEX/TIMEX Stat	2	1	1	V	n/a		0	1
Activation status of CAMEX/TIMEX power									
RAW VALUE		MEANING							
0		Not Active							
1		Active							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0150	TestPulseStatus	2	1	1	V	n/a		0	1
This parameter is used to enable/disable the Test Pulse									
RAW VALUE		MEANING							
0		Disabled							
1		Enabled							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0151	TestSwitch3 Stat	2	1	1	V	n/a		0	1
This parameter is used to enable/disable the Test Switch 3									
RAW VALUE		MEANING							
0		Disabled							
1		Enabled							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0152	TestSwitch2 Stat	2	1	1	V	n/a		0	1
This parameter is used to enable/disable the Test Switch 2									
RAW VALUE		MEANING							
0		Disabled							
1		Enabled							

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3

Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0153	TestSwitch1 Stat	2	1	1	V	n/a		0	1
This parameter is used to enable/disable the Test Switch 1									
RAW VALUE		MEANING							
0		Disabled							
1		Enabled							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0154	CAMEX 2 GainStat	2	1	1	V	n/a		0	1
Status of the CAMEX 2 Gain									
RAW VALUE		MEANING							
0		Low							
1		High							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0155	CAMEX 1 GainStat	2	1	1	V	n/a		0	1
Status of the CAMEX 1 Gain									
RAW VALUE		MEANING							
0		Low							
1		High							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0156	CAMEX 0 GainStat	2	1	1	V	n/a		0	1
Status of the CAMEX 0 Gain									
RAW VALUE		MEANING							
0		Low							
1		High							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0157	HexComDataShowSt	2	1	1	V	n/a		0	1
This parameter sets if Hexadecimal Command Data received at EPCE input are shown with Acknowledge									
RAW VALUE		MEANING							
0		Not Selected							
1		Selected							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0158	ReceivCommShowSt	2	1	1	V	n/a		0	1
This parameter sets if High Level Form Command received at EPCE input are shown with Acknowledge									
RAW VALUE		MEANING							
0		Not Selected							
1		Selected							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0159	TranHKDataShowSt	2	1	1	V	n/a		0	1
This parameter sets if the Hex HK Data transmitted from EPCE are shown									
RAW VALUE		MEANING							
0		Not Selected							
1		Selected							
PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0160	TraTabDataShowSt	2	1	1	V	n/a		0	1
This parameter sets if the Hex Table Data transmitted from EPCE are shown									
RAW VALUE		MEANING							
0		Not Selected							
1		Selected							

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3

Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0161	TransComShowStat	2	1	1	V	n/a		0	1

This parameter sets if the High Level Form Commands transmitted from EPCE to EPEA are shown

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0162	RecHKDataShowSt	2	1	1	V	n/a		0	1

This parameter sets if the Hex HK Data received at EPCE input from EPEA are shown

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0163	RecTabDataShowSt	2	1	1	V	n/a		0	1

This parameter sets if the Hex Table Data received at EPCE from EPEA are shown

RAW VALUE	MEANING
0	Not Selected
1	Selected

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0164	Patch Pointer	2	0	16	V	n/a		0	2

This parameter sets the location address to be pointed in the EPEA/EPCE S/W patch

RAW VALUE	MEANING
0	PROMTabEntry
1	EntryByNumb.
2	EntryByAddr.

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0165	EntryNumID/AddSe	3	12	16	V	n/a			

This parameter sets the Entry Number Identifier (if F0164=1) or the Entry Address Segment (if F0164=2) in the EPEA/EPCE S/W patch

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0166	EntryAddressOffs	3	12	16	V	n/a			

This parameter sets the Entry Address Offset in the EPEA/EPCE S/W patch if F0164=2, otherwise it is not meaningful

CALIBRATION CURVE

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0167	HBR1 Quadrant ID	2	2	2	V	n/a		0	3

This number identifies the selected quadrant in HBR 1

RAW VALUE	MEANING
-----------	---------

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0168	HBR2 Quadrant ID	2	2	2	V	n/a		0	3

This number identifies the selected quadrant in HBR 2

RAW VALUE	MEANING
-----------	---------

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0169	HBR3 Quadrant ID	2	2	2	V	n/a		0	3

This number identifies the selected quadrant in HBR 3

RAW VALUE	MEANING
-----------	---------

EPCS TC PARAMETER DETAILED LIST

EPIC-EST-TN-005 I.3
Appendix E

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0170	HBR4 Quadrant ID	2	2	2	V	n/a		0	3

This number identifies the selected quadrant in HBR 4

RAW VALUE	MEANING
------------------	----------------

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0171	HBR1QuadrantMode	2	2	2	V	n/a		0	3

Selected quadrant mode for HBR 1

RAW VALUE	MEANING
0	Normal
3	Transparent

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0172	HBR2QuadrantMode	2	2	2	V	n/a		0	3

Selected quadrant mode for HBR 2

RAW VALUE	MEANING
0	Normal
3	Transparent

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0173	HBR3QuadrantMode	2	2	2	V	n/a		0	3

Selected quadrant mode for HBR 3

RAW VALUE	MEANING
0	Normal
3	Transparent

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
F0174	HBR4QuadrantMode	2	2	2	V	n/a		0	3

Selected quadrant mode for HBR 4

RAW VALUE	MEANING
0	Normal
3	Transparent

PREF	NAME	PTC	PFC	WIDTH	FIX/VAR	UNIT	DEFAULT	MINIMUM	MAXIMUM
FIX		0	0	99	F	none	0	0	0

RAW VALUE	MEANING
------------------	----------------